ECO1850BO Product description: cylindrical 1850 litre bunded oil tank					
Minimum Base Required Diameter 2030mm		1430mm 500mm 500mm 500mm 600mm 50mm 50mm 50mm 195mm 50mm 10mm 50mm 10mm 50mm			
Product Information					

Froduct mormation					
Height	Diameter	Outlet	Fill Point	Weight	Security
2022mm	1430mm	1" BSP bottom	2" overfill prevention valve	125kg	Lockable lid

PRODUCT DETAILS:

- Suitable for the storage of Kerosene (C1/C2), Fuel Oil (A2) and GasOil/Diesel (D) as defined in BS2869 and BSEN590 including up to 10% biofuel to BSEN14214
- Bund contains minimum 110% volume of the inner tank
- Made from UV stabilised virgin polymer
- Designed and manufactured in the UK
- Bunded oil storage to protect the environment
- 4" inspection cap

BENEFITS:

- Economical high capacity oil storage
- Suitable for domestic, agricultural, & industrial use
- High impact strength
- Bunded construction offers integral protection from leakage and overfilling
- Covered bund prevents collection of rainwater & debris
- Rotationally moulded for strength and durability
- 10 year warranty against manufacturing defects

OPTIONAL EXTRAS:

- Alarms
- Filter valve pack
- Electronic level gauge
- Bund alarm
- Tigerloop and Tigerloop Kit
- Spill kit
- Fire valves
- Qual oil pipe
- Top outlet
- Colour options (Ecostone range)





Sizes approximate, owing to shrinkage

Etills Ltd Unit 1 Whiting Way, Melbourn, Royston, SG8 6NA

Tel: 01763 261781 Fax: 01763 268409

This specification may be subject to change without notice; please call to confirm details.